



## FEATURES

- Universal 85-264VAC or 120-370VDC input voltage
- Accepts AC or DC input (dual-use of same terminal)
- Operating ambient temperature range -40℃ to +70℃
- High I/O isolation voltage up to 4000VAC
- Industrial-grade design
- OVC III (design refer to EN61558-1: 2005)
- Low standby power consumption, high efficiency
- Low ripple & noise
- Output short circuit, over-current, over-voltage protection
- Withstand 300VAC surge input for 5s
- DIN rail TS35X7.5/ TS35X15 mountable

LI30-20BxxPR2 is Mornsun's AC-DC series featuring a cost-effective, energy efficient solution for standard DIN-rail mounting. The products offer a high level of stability and immunity to noise, compliant with IEC62368 standards for EMC and safety specifications meet IEC/EN61000-4, CISPR32, EN55032, IEC62368 and EN62368. These light weight AC-DC converters also have an extremely compact design for space saving and are ideal for applications such as industrial control equipment machinery and all kinds of applications in a harsh environment.

## Selection Guide

Certification	Part No.	Output Power (W)	Nominal Output Voltage and Current (Vo/Io)	Output Voltage Adjustable Range ADJ (V)*	Efficiency at 230VAC (%) Typ.	Capacitive Load (μF) Max.
EN/IEC/BIS	LI30-20B05PR2	15	5V/3A	4.9-5.5	82	12000
	LI30-20B12PR2	24	12V/2A	10.8-13.8	88	6000
	LI30-20B15PR2	30	15V/2A	13.5-18.0	89	5000
	LI30-20B24PR2	36	24V/1.5A	21.6-29.0	88	1400
	LI30-20B48PR2	36	48V/0.75A	43.2-55.2	90	600

Note: \*The actual adjustment range may extend outside the values stated, care should be exercised to ensure that the output voltage and power levels remain within the published maximum values.

## Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Voltage Range	AC Input	85	--	264	VAC
	DC Input	120	--	370	VDC
Input Frequency		47	--	63	Hz
Input Current	115VAC	--	--	0.9	A
	230VAC	--	--	0.5	
Inrush Current	115VAC	--	25	--	
	230VAC	--	45	--	
Leakage Current	264VAC	0.25mA RMS max.			
Hot Plug		Unavailable			

## Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	0% - 100% load	--	±2	--	%
Line Regulation	Rated load	--	±0.5	--	
Load Regulation	230VAC	--	±1.5	--	
Output Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	5V output	--	80	mV
		12V output	--	120	
		15V output	--	120	
		24V output	--	150	

# AC/DC 30W DIN-Rail Power Supply

## LI30-20BxxPR2 Series

**MORNSUN®**

		48V output	--	--	240	
Temperature Coefficient			--	±0.02	--	%/°C
Short Circuit Protection			Hiccup, continuous, self-recovery			
Over-current Protection			≥120 % Io, self-recovery			
Over-voltage Protection	5V output		≤7.5V	Output voltage clamp or hiccup		
	12V output		≤16V			
	15V output		≤20V			
	24V output		≤36V			
	48V output		≤60V			
Minimum Load			0	--	--	%
Start-up Time			--	--	3	s
Hold-up Time	115VAC		--	12	--	ms
	230VAC		--	60	--	

Note: \*The "parallel cable" method is used for ripple and noise test, please refer to AC-DC Converter Application Notes for specific information.

### General Specifications

Item		Operating Conditions		Min.	Typ.	Max.	Unit
Isolation	Input - output	Electric Strength Test for 1min., (leakage current<5mA)		4000	--	--	VAC
Operating Temperature				-40	--	+70	℃
Storage Temperature				-40	--	+85	
Storage Humidity				--	--	95	%RH
Operating Altitude				--	--	2000	m
Switching Frequency				--	65	--	kHz
Power Derating	-40℃ to -30℃	5V/48V output	3.0	--	--	% /℃	
		12V/15V output	7.0	--	--		
		24V output	5.0	--	--		
	+50℃ to +70℃		2.5	--	--	% /VAC	
	85VAC - 100VAC		1.0	--	--		
Safety Standard				IEC62368-1, IS13252 (Part1) safety approved & EN62368-1, EN IEC61558-1: 2019, EN61558-2-16: 2009, BS EN62368-1 (Report);			
Safety Class				CLASS II			
MTBF		MIL-HDBK-217F@25℃		> 300,000 h			

### Mechanical Specifications

Case Material	Plastic, heat-resistant (UL94V-0)
Package Dimensions	92.66 x 35.00 x 58.00 mm
Weight	115g (Typ.)
Cooling Method	Free air convection

### Electromagnetic Compatibility (EMC)

Emissions	CE	CISPR32/EN55032	CLASS B	
	RE	CISPR32/EN55032	CLASS B	
Immunity	ESD	IEC/EN61000-4-2	Contact ±6KV/Air ±8KV	Perf. Criteria A
	RS	IEC/EN61000-4-3	10V/m	Perf. Criteria A
	EFT	IEC/EN61000-4-4	±2KV	Perf. Criteria A
	Surge	IEC/EN61000-4-5	line to line ±2KV	Perf. Criteria A
	CS	IEC/EN61000-4-6	10Vr.m.s	Perf. Criteria A
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11	100% dip 1 periods, 30% dip 25 periods, 100% interruptions 250 periods	Perf. Criteria A

**MORNSUN®**



MORNSUN Guangzhou Science & Technology Co., Ltd.

2024.07.18-B/0



Page 2 of 4

MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation

### Product Characteristic Curve





Note: ① With an AC input between 85-100VAC and a DC input between 120-140VDC, the output power must be derated as per temperature derating curves;  
② This product is suitable for applications using natural air cooling; for applications in closed environment please consult Mornsun FAE.



### Dimensions and Recommended Layout

THIRD ANGLE PROJECTION



Pin-Out	
Pin	LI30-20B
1	AC(N)
2	AC(L)
3	-Vo
4	+Vo

Note:  
Unit: mm[inch]  
ADJ: adjustable resistance to change output voltage  
Wire range: 24-12 AWG  
Tightening torque: Max 0.4 N·m  
Mounting rail: TS35  
General tolerances:  $\pm 1.00[\pm 0.039]$

Note:

1. For additional information on Product Packaging please refer to [www.mornsun-power.com](http://www.mornsun-power.com). Packaging bag number: 58220195;
2. Unless otherwise specified, parameters in this datasheet were measured under the conditions of  $T_a=25^{\circ}\text{C}$ , humidity<75% with nominal input voltage and rated output load;
3. All index testing methods in this datasheet are based on our company corporate standards;
4. We can provide product customization service, please contact our technicians directly for specific information;
5. Specifications are subject to change without prior notice.
6. Products are related to laws and regulations: see "Features" and "EMC";
7. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China  
Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: [info@mornsun.cn](mailto:info@mornsun.cn) [www.mornsun-power.com](http://www.mornsun-power.com)