



FEATURES

- Universal 180 - 277VAC or 250 - 380VDC Input voltage
- Accepts AC or DC input (dual-use of same terminal)
- Operating ambient temperature range: -40°C to +70°C
- High reliability, efficiency up to 94%
- DC OK function
- High I/O isolation test voltage up to 4000VAC
- Output short circuit, over-current, over-voltage, over-temperature protection
- Operating altitude up to 5000m
- Over-voltage class II(designed to meet EN62368)
- Safety according to IEC/EN/UL/BS EN62368
- 3 years warranty

LM1500-22Bxx series is one of Mornsun's enclosed AC-DC switching power supply. It features universal AC input and at the same time accepts DC input voltage, cost-effective, high efficiency, high reliability and double or reinforced insulation. These converters offer excellent EMC performance and meet IEC/EN/UL/BS EN62368, GB4943 standards and they are widely used in areas of industrial, LED, street light control, electricity, security, telecommunications, smart home etc.

Selection Guide

Certification	Part No.*	Cooling Method*	Output Power (W)*	Nominal Output Voltage and Current (Vo/Io)	Output Voltage Adjustable Range ADJ(V)	Efficiency at 230VAC (%) Typ.*	Max. Capacitive Load (µF)
--	LM1500-22B12	Air blowing	1500	12V/125A	11.4-13.8	91.0	40000
	LM1500-22B15			15V/100A	14.25-17.25	91.0	20000
	LM1500-22B24			24V/62.5A	22.8-27.6	93.0	10000
	LM1500-22B27			27V/55.6A	25.65-31.05	93.0	8000
	LM1500-22B36			36V/41.67A	34.2-41.4	93.0	6000
	LM1500-22B48			48V/31.25A	45.6-55.2	94.0	5000
	LM1500-22B54			54V/27.78A	51.3-58	94.0	4000

Note: 1.*Use suffix "QQ" for both sides conformal coating;
 2. *Under any conditions, the total power of the product should not exceed the rated power. When the output voltage is increased, the total output power cannot exceed the rated output power, when the output voltage is decreased, the output current cannot exceed the rated output current;
 3. *Wind blows from the outside into the product.

Input Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Input Voltage Range	Rated input (Certified voltage)		200	--	240	VAC
	AC input		180	--	277	
	DC input		250	--	380	VDC
Input Voltage Frequency	Rated input (Certified voltage)		47	--	63	Hz
	AC input		47	--	63	
Input Current	200VAC		--	10	--	A
	230VAC		--	8	--	
Inrush Current	230VAC		--	40	--	
Power Factor	230VAC		--	--	0.95	--
Leakage Current	240VAC, 60Hz	Earth leakage current	--	--	5	mA
		Touch current	--	--	0.5	
Hot Plug			Unavailable			

Output Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Output Voltage Accuracy	Full load range		--	±1.0	--	%
Line Regulation	Rated load		--	±0.5	--	
Load Regulation	0% - 100% load		--	±0.5	--	
Minimum Load			0	--	--	
Ripple & Noise*	20MHz bandwidth (peak-peak value)	12V/15V/24V/27V	--	--	150	mV
		36V/48V/54V	--	--	200	
Temperature Coefficient			--	±0.03	--	%/°C
Hold-up Time	230VAC, rated load		--	12	--	ms
Short Circuit Protection	Recovery time <30s after the short circuit disappear.		Turn off, continuous, self-recover			
Over-current Protection	230VAC, rated load	Normal temperature, high temperature	130% - 200% Io, hiccup, constant current mode, shut down after 1s, self-recover			
		Low temperature	≥130% full load after derating, hiccup, constant current mode, shut down after 1s, self-recover			
Over-voltage Protection	12V		≤16.2VDC (Output voltage hiccup, self-recover)			
	15V		≤25VDC (Output voltage hiccup, self-recover)			
	24V		≤35VDC (Output voltage hiccup, self-recover)			
	27V		≤35VDC (Output voltage hiccup, self-recover)			
	36V		≤50VDC (Output voltage hiccup, self-recover)			
	48V		≤63VDC (Output voltage hiccup, self-recover)			
	54V		≤63VDC (Output voltage hiccup, self-recover)			
Over-temperature Protection	230VAC, 100% load	Over-temperature protection start	--	70	--	°C
		Over-temperature protection release	50	--	--	

Note: *The "Tip and barrel method" is used for ripple and noise test, output parallel 47uF electrolytic capacitor and 0.1uF ceramic capacitor, please refer to Enclosed Switching Power Supply Application Notes for specific information.

General Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Isolation Test	Input - ⊕	Electric strength test for 1min., leakage current <5mA	2000	--	--	VAC
	Input - output		4000	--	--	
	Output - ⊕		1250	--	--	
Insulation Resistance	Input - ⊕	Ambient temperature: 25 ± 5°C Relative humidity: < 95%RH, no condensation Test voltage: 500VDC	100	--	--	MΩ
	Input - output		100	--	--	
	Output - ⊕		100	--	--	
Operating Temperature			-40	--	70	°C
Storage Temperature			-40	--	85	
Operating Humidity	Non-condensing		10	--	95	%RH
Storage Humidity			20	--	90	
Power Derating	Operating temperature derating	-40°C to -30°C	5	--	--	% / °C
		+50°C to +70°C	2	--	--	
	Input voltage derating	180VAC-200VAC	0.5	--	--	%/VAC
Safety Standards			Design refer to UL/EN/IEC 62368-1, GB4943.1			
Safety Class			CLASS I			
MTBF	MIL-HDBK-217F@25°C		≥354,000 h			
Warranty	Ambient temperature: <50°C		3 years			

Functional Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
DC_OK Signal	All input voltage range, all load range	Power on	80	90	95	%Vo
Remote Sense	S-(CON3) and S+(CON4) of the terminal (CON) are remote compensation function pins connected to both ends of the output load (S+ is connected to Vo+, S- is connected to Vo-).					
Remote Control Switch*	RC-(CON5) and RC+(CON6) of the terminal (CON) are the pins of the remote control switch function, and external voltage is required when used (RC+ is connected to Vout, RC- is connected to GND).					
	All input voltage range, all load range	Power on	0	--	0.8	V
		Power off	4	--	10	

Note: *Power is on when the remote switch pins are left open.

General Specifications

Case Material	SUS 304		
Dimensions	250.00mm x 127.00mm x 40.50mm		
Weight	12V/15V	1550g (Typ.)	
	24V/27V/36V/48V/54V	1450g (Typ.)	
Cooling Method	Forced air cooling 17.15CFM		

Electromagnetic Compatibility (EMC)

Emissions	CE (Input port)	CISPR32 EN55032	150K - 30MHz	CLASS A
	RE	CISPR32 EN55032	30MHz - 1GHz	CLASS A
Immunity	ESD	IEC/EN61000-4-2	Contact ±6KV/Air ±8KV	perf. Criteria A
	RS	IEC/EN61000-4-3	10V/m	
	EFT (Input port)	IEC/EN61000-4-4	±4KV	
	Surge (Input port)	IEC/EN61000-4-5	line to line ±2KV/line to ground ±4KV	
	MS	IEC/EN61000-4-8	30A/m	
	CS	IEC/EN61000-4-6	0.15 - 80MHz 20Vr.m.s	
	Voltage dips	IEC/EN61000-4-11	0% of 200Vac, 0Vac, 1 cycle	
40% of 100Vac, 80Vac, 10/12 cycle			perf. Criteria C	
70% of 100Vac, 140Vac, 25/30 cycle			perf. Criteria B	

Note: 1. *perf. Criteria:

A: The equipment shall continue to operate as intended without operator intervention;

B: After the test, the equipment shall continue to operate as intended without operator intervention;

C: Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions.

2. *The power supply does not meet the requirements of harmonic current stipulated in EN61000-3-2; This power supply is not suitable for the following situations.

1) The terminal equipment is used in the European Union.

2) The terminal equipment is connected to public mains supply with 220VAC or greater rated nominal voltage that mandatory to meet the requirements of EN61000-3-2.

3) The power supply is installed in terminal equipment with average or continuous input power greater than 75W.

4) The power supply belong to a part of lighting system.



In addition, the power supply can be used in the following terminals which do not need to meet EN61000-3-2;

(1) Professional equipment with total fixed input power greater than 1000W;



(2) symmetrical controlled heating element with rated power less than or equal to 200W.

3. *If no harmonic current is required or customers can solve harmonic current problems by themselves, this product can be used.

Product Characteristic Curve




- Note: 1. With an AC input voltage between 180-200VAC and a DC input between 254-282VDC the output power must be derated as per the temperature derating curves;
 2. This product is suitable for applications using forced air cooling; for applications in closed environment please consult Mornsun FAE.




Typical Application

1. Remote ON/OFF




- Note: 1. When the product is working normally, apply voltage (5-15V) to RC+ and RC- to trigger the remote ON/OFF function, and the output voltage will be off. Withdraw the voltage, the output voltage will be re-established;
 2. 5V standby power supply is not controlled by remote ON/OFF function.

2. DC_OK



- Note: 1. When the output voltage of the product reaches 90% of the rated value, DC_OK+ will be connected to DC_OK- ;
 2. It is recommended that users apply a certain voltage between DC_OK+ and DC_OK- to detect the signal.


3. Remote Sense Compensation



- Note: 1. The left side represents the internal schematic diagram of the product, the right side represents the customer system;
 2. Twisted pair wires are needed for S+/S-;
 3. If the Pin14 terminal function is used for long-term matching, please glue to secure it.


Installation Diagram

Standard mounting orientation:




Note: The fan panel cannot be blocked by other objects, and a distance of at least 20mm must be maintained, otherwise it will affect the heat dissipation and performance of the power module.

Position of mounting holes:



Dimensions and Recommended Layout



Note:
Unit: mm[inch]
ADJ: Output adjustable resistor
LED: Output status indicator LED
General tolerances: ± 1.00[± 0.039]
Unmarked dimensions refer to the actual product
The fan panel cannot be blocked by other objects, and a distance of at least 20mm must be maintained

Note:

- For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging bag number: 58220735
- Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25°C, humidity <75%RH with nominal input voltage and rated output load;
- The room temperature derating of 5°C/1000m is needed for operating altitude greater than 2000m;
- All index testing methods in this datasheet are based on our company corporate standards;
- In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
- We can provide product customization service, please contact our technicians directly for specific information;
- Products are related to laws and regulations: see "Features" and "EMC";
- The out case needs to be connected to PE (⊕) of system when the terminal equipment in operating;
- The output voltage can be adjusted by the ADJ, clockwise to increase;
- Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units;
- The power supply is considered a component which will be installed into a terminal equipment. All EMC tests should be confirmed with the final equipment. Please consult our FAE for EMC test operation instructions.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China
Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: info@mornsun.cn www.mornsun-power.com