

40W isolation DC-DC converter with ultra-wide, ultra-high 200 - 1500VDC input for Renewable Energy



#### **FEATURES**

- Ultra wide input voltage range: 200 1500VDC
- Industrial grade operating temperature: -40  $^\circ\!{\rm C}$  to +70  $^\circ\!{\rm C}$
- High I/O isolation voltage up to 4000VAC
- High efficiency, low ripple & noise
- Input under-voltage protection, input reverse polarity protection, output short circuit, over-current, over-voltage protection

 Safety according to UL1741, CSA-C22.2 No.107.1, EN62109

PV40-29B28 is regulated DC-DC converters with an ultra-wide DC input of 200-1500VDC. The products feature high efficiency, high reliability, high insulation and high level of safety. This type of power supply is widely used in renewable energy industries such as photovoltaic, power generation, energy storage, inverters and high-voltage DC conversions. The converters provide multiple protection features and guarantee stable and safe operating environments even under abnormal working conditions. For extremely harsh EMC environment, we recommend using the application circuit show in Design Reference of this datasheet.

Selection Guide							
Part No.	Output Power	Nominal Output Voltage and Current (Vo/Io)	Efficiency at 800VDC (%) Typ.	Capacitive Load (µF) Max. (Normal temperature full load)			
PV40-29B28	40W	28V/1430mA	83	470			

Input Specifications						
Item	Operating Conditions	Min.	Тур.	Max.	Unit	
Input Voltage Range		200		1500	VDC	
	200VDC			320	mA	
Input Current	800VDC			80		
	1500VDC			42		
Inrush Curront	200VDC		50		A	
Inrush Curreni	1500VDC		150			
Under-voltage Protection		Lockout activation range: 170 - 185V Lockout deactivation range: 180 - 195V		- 185V 0 - 195V		
External Input Fuse Required		4A/1500VD	C, required			
Hot Plug		Unavailable				

Output Specifications							
Item	Operating Conditions	Min.	Тур.	Max.	Unit		
Output Voltage Accuracy			±2				
Line Regulation	Full load		±l		%		
Load Regulation	0% - 100% load		±l				
Ripple & Noise*	20MHz bandwidth (peak-to-peak value)		150	300	mV		
Temperature Coefficient			±0.02	±0.15	<b>%/</b> ℃		
Short Circuit Protection		Continuous, self-recovery					
Over-current Protection	iction ≥110%lo, self-recovery						
Over-voltage Protection		≤35VDC					
Minimum Load		0			%		
Start-up Delay Time**	200 - 1500VDC			3	S		

Note: \* The "parallel cable" method is used for ripple and noise test, please refer to AC-DC Converter Application Notes for specific information.

\*\* Full input voltage / output load range (The cooling-time between input power-off and power-on again is greater than 15s).

**MORNSUN**<sup>®</sup>

### DC/DC Converter PV40-29B28

# MORNSUN®

General Specifications								
ltem		Operating Conditions		Min.	Тур.	Max.	Unit	
Isolation	Input-output	Electric Strength Test fo	or 1 min.	4000			VAC	
Operating Tempe	ərature			-40		+70	ĉ	
Storage Tempero	iture			-40		+85		
Storage Humidity	,					95	%RH	
Soldering Temperature		Wave-soldering			260 ± 5°C; time: 5 - 10s			
		Manual-welding			360 ± 10°C; time: 3 - 5s			
		-40°C to 0°C	200 - 300VDC	1.50			9/10	
Der von Denette er		+50°C to +70°C		2.50			<b>/0/</b> C	
Power Derating		1200VDC-1500VDC		0.07			%/VDC	
		2000m - 5000m		6.70			%/Km	
Switching Frequency					65		kHz	
Safety Standard				Design refe EN62109	Design refer to UL1741, CSA-C22.2 No.1 EN62109		0.107.1 &	
Altitude						5000	m	
MTBF				MIL-HDBK-2	217F@25℃≥	300,000 h		

Mechanical Specifications				
Case Material	Black flame-retardant and heat-resistant plastic (UL94 V-0)			
Dimensions	125.00 x 75.00 x 40.00 mm			
Weight 434g (Typ.)				
Cooling Method	Free air convection			

Electromagnetic Compatibility (EMC)							
Emissions	CE	CISPR32/EN55032	CLASS A (See Fig. 2 for recommended circuit)				
ETTISSIONS	RE	CISPR32/EN55032	CLASS A (See Fig. 2 for recommended circuit)				
	ESD	IEC/EN61000-4-2	Contact ±6KV/Air ±8KV	Perf. Criteria B			
	RS	IEC/EN61000-4-3	10V/m	Perf. Criteria A			
Impound to (	EFT	IEC/EN61000-4-4	±2KV (See Fig. 2 for recommended circuit)	Perf. Criteria B			
Infinanity	Surge	IEC/EN61000-4-5	line to line±1KV (See Fig. 2 for recommended circuit)	Perf. Criteria B			
	CS	IEC/EN61000-4-6	10Vr.m.s	Perf. Criteria A			
	PFM	IEC/EN61000-4-8	10A/m	Perf. Criteria A			

#### Product Characteristic Curve





**MORNSUN®** 

## DC/DC Converter PV40-29B28

## MORNSUN®



Note:

① With an input between 1200 - 1500VDC, the output power of PV40-29B28 parts must be derated as per temperature derating curves; ② For operation of this converter series in an altitude between 2000 - 5000m above sea level, the output power must be derated as per the altitude derating curve;

③ This product is suitable for applications using natural air cooling; for applications in closed environment please consult Mornsun FAE.



#### **Design Reference**

1. Typical application



Fig. 1: Typical application circuit

Note on filter components:

We recommend using an electrolytic capacitor with high frequency and low ESR rating for C2 (refer to manufacture's datasheet). C1 is a ceramic capacitor, used to filter high-frequency noise. Choose a capacitor voltage rating with at least 20% margin, in other words not exceeding 80%. TVS is a recommended suppressor diode to protect the application in case of a converter failure.

#### 2. EMC compliance recommended circuit



Fig 2: EMC application for higher compliance requirements (output parameters are show in Figure 1)

**MORNSUN®** 

Component	Recommended value		
C7/C8/C9/C10	Safety capacitor 104K/275VAC		
C3/C4/C5/C6	47uF/450VDC		
R1/R2/R3/R4	1M Ω /2W		
LDM	330uH/1A		
LCM	7mH/1A		
FUSE	4A/1500VDC, required		

3. Trim Function for Output Voltage Adjustment (open if unused)



TRIM resistor connection (dashed line shows internal resistor network)

Calculating Trim resistor values:

up: 
$$R_T = \frac{aR_2}{R_2 - a} - R_3$$
  $a = \frac{Vref}{Vot - Vref} \cdot R_1$   
down:  $R_T 1 = \frac{aR_1}{R_1 - a} - R_3$   $a = \frac{Vot - Vref}{Vref} \cdot R_2$ 

 $R_T/R_T$  1= Trim Resistor value; a = Self-defined parameter;

Vout	R1(K Ω )	R2(K Ω )	R3(K Ω )	Vref(V)	Vot(V)
28V	10	0.97	2	2.5	Resulting trimmed output voltage, range $\leqslant \pm 10\%$

Note:  $R_{T}1{=}150k\,\Omega$  , output is 26.4V/1.515A.

4. For additional information please refer to application notes on <u>www.mornsun-power.com.</u>



## DC/DC Converter PV40-29B28

Dimensions and Recommended Layout



#### Note:

- 1. For additional information on Product Packaging please refer to <u>www.mornsun-power.com</u>. Packaging bag number of Horizontal package: 58020023;
- 2. Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25°C, humidity<75% with nominal input voltage and rated output load;
- 3. All index testing methods in this datasheet are based on our company corporate standards;
- 4. In order to improve the efficiency, there will be audible noise generated when working at input voltage higher than 1000 VDC, but it does not affect product performance and reliability;
- 5. It is recommended that the product be locked screw before welding;
- 6. The above are the performance indicators of the product models listed in this datasheet. Some indicators of non-standard models will exceed the above requirements. For details, please contact our technical staff.
- 7. We can provide product customization service;
- 8. Products are related to laws and regulations: see "Features" and "EMC";
- 9. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

## Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China<br/>Tel: 86-20-38601850Fax: 86-20-38601272E-mail: info@mornsun.cnwww.mornsun-power.com



MORNSUN Guangzhou Science & Technology Co., Ltd.

**MORNSUN**<sup>®</sup>