# **MORNSUN**<sup>®</sup>

Single universal CAN isolation transceiver module

CE Report

**RoHS** 

## **FEATURES**

- Integrated high efficiency isolated DC/DC converter
- Two-port isolation (3kVDC)
- High baud rate up to 1Mbps
- Operating ambient temperature range: -40 $^{\circ}$ C to +105 $^{\circ}$ C
- Complies with ISO 11898 standard
- An unpowered node does not disturb the bus lines
- The bus supports maximum 110 nodes
- Set isolation and ESD bus protection in one

The TD301DCAN/TD501DCAN series' main function is to convert TTL / CMOS level into isolated CAN bus differential level signals. The use of IC integrated technology allows for power isolation, signal isolation, CAN transceiver and bus protection all in one single CAN bus transceiver module, which withstands an isolation test voltage of 3000VDC. Also, they can easily be embedded in the user's end equipment, to achieve fully functional CAN bus network connectivity.

Selection Guide							
Certification	Part No.	Power input (VDC)	Baud Rate (bps)	Static Current (mA)	Maximum Operating Current(mA)	Bus Maximum Voltage(VDC)	Number of Nodes
EN	TD301DCAN	3.3	5k-1M	50	90	±30	110
	TD501DCAN	5	5k-1M	35	80	±30	110

Absolute Limits						
Item	Operating Conditions	Min.	Тур.	Max.	Unit	
Input Surge Voltage (1000 mgy)	3.3V series	-0.7		5		
Input surge voltage (Tsec.max.)	5V series	-0.7		7	VDC	
Pin Soldering Temperature	Soldering spot 1.5mm away from case, 10s max.			300	°C	

3.3V Series inp	out Specifi	cations				
Item		Symbol	Min.	Тур.	Max.	Unit
Power Supply Input Voltage		VCC	3.15	3.3	3.45	
	High-level	VIH	0.7Vcc		Vcc+0.5	
Logic Level		Vil	0		0.8	VDC
RXD Logic Level	High-level	Vон	Vcc-0.4	Vcc-0.2		-
	Low-level	Vol		0.2	0.4	
TXD Drive Current		Γ	2			~^
RXD Output Current		IR			10	ШA
Serial Interface		Standard CAN controller interface for +3.3V				

5V Series Input Specifications						
Item		Symbol	Min.	Тур.	Max.	Unit
Power Supply Input Voltage		VCC	4.75	5	5.25	
TXD Logic Level	High-level	VIH	0.7Vcc		Vcc+0.5	VDC
	Low-level	VL	0		0.8	
RXD Logic Level	High-level	Vон	Vcc-0.4	Vcc-0.2		
	Low-level	VoL	-	0.2	0.4	
TXD Drive Current		п	2			~^^
RXD Output Current		IR	-		10	mA
Serial Interface		Standard CAN controller interface for +5V				

**MORNSUN®** 

MORNSUN Guangzhou Science & Technology Co., Ltd.

MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation

# Industrial Bus TD5(3)01DCAN Series

# **MORNSUN**<sup>®</sup>

Transmission Specifications							
Item		Symbol	Min.	Тур.	Max.	Unit	
Data Delay	TXD Transmitter Delay	τ		60	115		
	RXD Receiver Delay	tr		70	135	ns	
	Cycle Delay	TPRO(TXD-RXD)		130	250		

## Output Specifications

Item		Symbol	Min.	Тур.	Max.	Unit
Dominant Level	CANH	V(OD)CANH	2.75	3.5	4.5	
(Logic 0)	CANL	V(OD)CANL	0.5	1.5	2	
Recessive Level	CANH	V(OR)CANH	2	2.5	3	
(Logic 1)	CANL	V(OR)CANL	2	2.5	3	
Differential Level	Dominant Level (Logic 0)	Vdiff(d)	1.5	2	3	VDC
	Recessive Level (Logic 1)	Valiff(r)	-0.12	0	0.05	
Bus Pin Maximum Withstand Voltage		Vx	-30		+30	
Bus Transient Voltage		Vtrt , Meet ISO7637-3 standard	-200		+200	
Load Resistance Differential		RL	50	60	65	Ω
Input Impedance Differential		Raiff	20		100	kΩ
CAN Bus Interface		Meets ISO/DIS 11898-2 standard twisted-pair output				
Note: The Recessi	ve level (Loaic 1) is the no-la	ad specification				

General Specifications				
Item	Operating Conditions	Value		
Isolation Test	Electric strength test for 1 min., leakage current <1mA	3kVDC		
Insulation Resistance	At 500VDC	1000M <sup>Ω</sup> (input-output)		
Operating Temperature		<b>-40</b> ℃ to +105℃		
Transportation and Storage Temperature		<b>-50</b> ℃ to +125℃		
Operating Humidity	Non-condensing	10% - 90%		
Safety Standard		EN62368-1 (Report)		
Safety Class		CLASS III		

Mechanical Specifications		
Case Material	Black flame-retardant heat-proof plastic (UL94 V-0)	
Dimensions	DIP8	
Weight	4.0g (Typ.)	
Cooling Method	Free air convection	

Electro	Electromagnetic Compatibility (EMC)				
Emission	CE	CISPR32/EN55032	CLASS A (see Fig. 3)		
	ESD	IEC/EN 61000-4-2	Contact ±4kV (without external components, Signal port)	Perf. Criteria B	
Immunity	EFT	IEC/EN 61000-4-4	±2kV (without external components, Signal port)	Perf. Criteria B	
	Surge	IEC/EN 61000-4-5	±2kV (line to ground) (without external components, Signal port)	Perf. Criteria B	
	CS	IEC/EN 61000-4-6	3Vr.m.s (without external components)	Perf. Criteria A	

**MORNSUN**<sup>®</sup>

MORNSUN Guangzhou Science & Technology Co., Ltd.

2025.04.22-B/2 Page 2 of 5 MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation

# Industrial Bus

## TD5(3)01DCAN Series

# **MORNSUN**<sup>®</sup>

## **Application Precautions**

- 1. Carefully read and follow the instructions before use; contact our technical support if you have any question;
- 2. Do not use the product in hazardous areas;
- 3. Use only DC power supply source for this product. 220V AC power supply is prohibited;
- 4. It is strictly forbidden to disassemble the product privately in order to avoid product failure or malfunction;
- 5. Hot-swap is not supported;
- 6. If the external input of TXD is insufficient, the pull-up resistor should be added according to the situation.

#### After-sales service

- 1. Factory inspection and quality control are strictly enforced before shipping any product; please contact your local representative or our technical support if you experience any abnormal operation or possible failure of the module;
- 2. The products have a 3-year warranty period, from the date of shipment. The product will be repaired or exchanged free of charge within the warranty period for any quality problem that occurs under normal use.

#### Applied circuit

Refer to the CAN Industrial Bus Interface Isolating Module Application Manual.

## Design Reference

1. Typical application circuit



Fig.1

Figure 1 shows a typical application circuit for connecting a module. The module with its integrated power supply, CAN controller and CAN bus network interface can generally be used by customers as is, without the need of adding peripheral circuits. Note: The logic level of the CAN controller should be compatible with the TD5(3)01DCAN.



Fig.2

As shown in Figure 2, a single CAN-bus network allows connecting as many as 110 isolated single-channel TD\_CAN transceiver modules. This universal type module supports a maximum communication distance of 10km while the high-speed type module can support a maximum communication distance of 1km with a baud rate beyond 40kbps. For accessing more nodes or achieving longer communication distances, CAN repeaters or other expansion equipment can easily be used.

Note: The communication distance of the bus is related to the communication speed and its field application. It can be designed according to the actual application and reference standard. We recommended the use of a twisted pair or shielded twisted pair as the communication cable and it should be kept away from any sources of interference. For long-distance communication, the terminal resistance value needs to be selected in accordance with the communication distance, the cable impedance and the number of nodes.

# **MORNSUN®**

MORNSUN Guangzhou Science & Technology Co., Ltd.

MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation

# Industrial Bus TD5(3)01DCAN Series





Component	Recommended part, value
C1, C2	1uF/16V
LDM	CD43-12uH

Fig.3

### 2. Recommended port protection circuit



Fig.4

Note: Ground shield of twisted wire pair reliably. Recommended components and values:

Component	Recommended part, value	Component	Recommended part, value
R3	1ΜΩ	R1, R2	2.7 Ω /2W
C1	1nF, 2kV	D1, D2	1N4007
TI	ACM2520-301-2P	D3	SMBJ30CA
GDT	B3D090L	Rterminal	<b>120</b> Ω

When the module is used in applications with harsh environment, it can be susceptible to large energy like lightning strike, etc. in which case, it is essential to add an adequate protection circuit to the CAN signal ports to protect the system from failure and maintain a reliable bus communication. Figure 4 provides a recommended protection circuit design for high-energy lightning surges, with a degree of protection related to the selected protection device. Parameter description lists a set of recommended circuit parameters, which can be adjusted according to the actual application situation. Also, when using the shielded cable, the reliable single-point grounding of the shield must be achieved.

Note: The recommended components that will change the Specifications of Bus Pin Maximum Withstand Voltage by D3 and its values is a general guideline only. It must be verified for the actual user's application. We recommended using PTC's for R1 and R2 and to use fast recovery diodes for D1 and D2. 3. For additional information, please refer to our application note on www.mornsun-power.com

**MORNSUN®** 

MORNSUN Guangzhou Science & Technology Co., Ltd.

2025.04.22-B/2 Page 4 of 5 MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation

# Industrial Bus TD5(3)01DCAN Series

## **Dimensions and Recommended Layout**



Note: 20.00 [0.787] -Unit: mm[inch] Pin1/2/3/4/5/6/7/8: Ø0.5mm Pin diameter tolerances:  $\pm 0.10[\pm 0.004]$ General tolerances:  $\pm 0.50[\pm 0.020]$ The layout of the device is for reference only, please refer to the actual product

Pin	Mark	Function
1	VCC	Input Power+
2	GND	GND
3	TXD	TD-DCAN Sending Pin
4	RXD	TD–DCAN Receiving Pin
6	CANH	TD-DCAN H Pin
7	CANL	TD-DCAN L Pin
8	CANG	Isolation Power Output CANG

#### Notes:

- 1. For additional information on Product Packaging please refer to <u>www.mornsun-power.com</u>. The Packaging bag number: 58040012;
- 2. Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25°C, humidity<75%RH with nominal input voltage and rated output load;
- 3. All index testing methods in this datasheet are based on company corporate standards;
- 4. The above are the performance indicators of the product models listed in this datasheet. Some indicators of non-standard models will exceed the above requirements. For details, please contact our technical staff;
- 5. We can provide product customization service, please contact our technicians directly for specific information;
- 6. Products are related to laws and regulations: see "Features" and "EMC";
- 7. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

# MORNSUN Guangzhou Science & Technology Co., Ltd.

Address: No. 8 Nanyun 4th Road, Huangpu District, Guangzhou, ChinaTel: 86-20-38601850Fax: 86-20-38601272E-mail: info@mornsun.cn

www.mornsun-power.com

**MORNSUN**<sup>®</sup>

### MORNSUN Guangzhou Science & Technology Co., Ltd.

2025.04.22-B/2 Page 5 of 5

MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation