


Signal conditioning modules



RoHS



FEATURES

- Two-port isolation (signal input and signal output)
- High accuracy of 0.1% Full Scale
- High linearity of 0.1% Full Scale
- Isolation test voltage 2kVAC for 60s
- Extremely low temperature coefficient of $\leq 50\text{PPM}/^\circ\text{C}$
- Industrial grade operating temperature range from -40°C to $+85^\circ\text{C}$
- High reliability, MTBF >500,000 hours
- Low ripple & noise: $\leq 35\text{mVpp}$, 20MHz
- ESD protection to IEC/EN61000-4-2, Contact $\pm 4\text{kV}$ with performance Criteria B
- Small footprint DIP Package 26 x 9.5 x 12.5mm
- Signal load capacity $\geq 2\text{k}\Omega$ (@ signal output 10V Max.)
- EN60950 approval

TEMxxxxAN series are analog signal isolation modules with incoming millivolt positive/negative signal input and transformed positive signal output. They are equipped with an efficient built-in micro-power source that supplies additionally power to the internal input signal circuitry. The adopted electromagnetic isolation technology has a better performance, a much higher accuracy and a lower temperature drift in comparison with photo/opto-coupler isolators. This type of product has in addition to low temperature drift and high linearity, a low power consumption and low ripple & noise. They have a two-terminal isolation from signal input to signal output/power input.

Selection Guide

Certification	Part No.	Power Supply Input Typ. (VDC)	Input Signal	Output Signal	Isolated Power Output (VDC)
CE	TEM5630AN	24VDC	$\pm 75\text{mV}$	0-5VDC	None
	TEM6650AN	12VDC	$\pm 100\text{mV}$	0-5VDC	None
	TEM6640AN	15VDC	$\pm 100\text{mV}$	0-5VDC	None

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit	
Power Input	Input voltage	Typ.-5%	Typ.	Typ.+5%	VDC	
	Input power	Signal full load	--	--	1.0	W
	Power supply protection		Input reverse polarity protection			
Signal Input	Input signal	See selection guide				
	Input impedance	in case of max. input of voltage signal	10	--	--	M Ω
	Over range		-10	--	+10	V

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit	
Signal Output	Output Signal	See selection guide				
	Load Capacity	Voltage output	2	--	--	K Ω
	Ripple & Noise	Bandwidth 20MHz	--	--	35	mVp-p

Transmission Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Zero Offset		-0.1%FS	--	+0.1%FS	--
Signal Precision		-0.1%FS	--	+0.1%FS	--
Temperature Coefficient	Operating temperature range from $-40 \sim +85^\circ\text{C}$	--	--	50	PPM/ $^\circ\text{C}$
Bandwidth		2	--	--	KHz
Response Time		--	--	1	ms

General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Electric Isolation		Power input and the signal output are on the common ground. Isolated between signal input terminal and signal output terminal.			
Isolation Test	Electric strength test for 1 minute with a leakage current <1mA, humidity <70%	2	--	--	KVAC
Isolation Resistance	At 500VDC	100	--	--	MΩ
Operating Temperature		-40	--	+85	°C
Transportation and Storage Temperature		-50	--	+105	°C
Case Temperature Rise	Ta=25°C	--	--	30	°C
Safety Standard		EN60950			
Safety Certification		EN60950			
Safety Class		CLASS III			
Application Environment		The presence of dust, severe vibration, shock and corrosive gas may cause damage to the product			

Mechanical Specifications

Case Material	Black plastic, flame-retardant heat- resistant
Package	DIP18
Weight	8g(Typ.)
Cooling Method	Free air convection

Electromagnetic Compatibility (EMC)

Immunity	ESD	IEC/EN61000-4-2	Contact ±4kV	perf. Criteria B
	EFT	IEC/EN61000-4-4	Signal input port ±1kV (see Fig. 3 for recommended circuit)	perf. Criteria B
	Surge	IEC/EN61000-4-5	Signal input port ±1kV (line-to-ground)(see Fig. 3 for recommended circuit)	perf. Criteria B

Application Precautions

1. Carefully read and follow the instructions before use; contact our technical support if you have any question;
2. Do not use the product in hazardous areas;
3. Use only DC power supply source for this product. 220VAC power supply is prohibited;
4. It is strictly forbidden to disassemble the product privately in order to avoid product failure or malfunction;

After-sales service

1. Factory inspection and quality control are strictly enforced before shipping any product; please contact your local representative or our technical support if you experience any abnormal operation or possible failure of the module;
2. The products have a 3-year warranty period, from the date of shipment. The product will be repaired or exchanged free of charge within the warranty period for any quality problem that occurs under normal use.

Applied circuit

Please refer to Isolated Transmitter Application Notes.

3. EMC compliance circuit





Fig. 3

Component	Recommended part, value
R1	12 Ω /2W
TVS1	SMBJ5CA

4. For additional information please find the application notes on www.mornsun-power.com

Dimensions and Recommended Layout



Notes:

- For additional information on Product Packaging please refer to www.mornsun-power.com. The Packaging bag number: 58240002;
- Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25°C, humidity<75%RH with nominal input voltage and rated output load.
- All index testing methods in this datasheet are based on company corporate standards;
- The above are the performance indicators of the product models listed in this datasheet. Some indicators of non-standard models will exceed the above requirements. For details, please contact our technical staff;
- We can provide product customization service;
- Products are related to laws and regulations: see "Features" and "EMC";
- Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

MORNSUN Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Luogang District, Guangzhou, P. R. China
Tel: 86-20-38601850-8801 Fax: 86-20-38601272 E-mail: info@mornsun.cn